



Keymark Certificate



078/000196

AENOR certifies that the organization

SUNEX, S.A.

registered office UL. PIASKOWA, 7 47-400 RACIBÓRZ (Polonia)

supplies **Solar collectors**

in compliance with UNE-EN 12975-1:2006+A1:2011 (EN 12975-1:2006+A1:2010)

Trade Mark AMX 2.0
Technical information Specified in Annexes to the Certificate

Production site UL. PIASKOWA, 7 47-400 RACIBÓRZ (Polonia)

Certification scheme In order to grant this Certificate, AENOR has tested the product and has verified the quality system implemented for its manufacture. AENOR performs these tasks periodically while the Certificate has not been cancelled, in accordance with Specific Rules RP 078.01.

First issued on 2013-05-06
Last issued on 2023-05-06
Validity 2028-05-06

Rafael GARCÍA MEIRO
CEO





Annex to Solar Keymark Certificate Supplementary Information	Licence Number	078/000196
	Issued	2023-05-06

Annual collector output in kWh/collector at mean fluid temperature ϑ_m													
Collector name	Standard Locations ϑ_m	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
AMX 2.0		2.295	1.612	1.075	1.723	1.197	789	1.268	826	519	1.380	891	551
Annual output per m ² gross area		1.140	800	534	856	594	392	630	410	258	685	442	274
Annual efficiency, η_a		65%	45%	30%	52%	36%	24%	54%	35%	22%	55%	36%	22%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18,5°C			3,2°C			7,5°C			9,0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (September 2019). A detailed description of the calculations is available at <http://www.estif.org/solarkeymarknew/>

Additional Information

Collector heat transfer medium	Water-Glycole
The collector is deemed to be suitable for roof integration	Yes
The collector was tested successfully under the following conditions:	
Climate class (A+, A, B or C)	C
G (W/m ²) >	850
ϑ_a (°C) >	10
H_x (MJ/m ²) >	420
Maximum tested positive load	1000 Pa
Maximum tested negative load	1000 Pa
Hail resistance using ice balls (diameter)	- mm

Additional collector attribute(s)

- Using external power source(s) for normal operation Active or passive measure(s) for self-protection
 Co-generating thermal and electrical power Façade collector(s)

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, A_{sol} (m ²)	Hydraulic Designation Code	Aperture Area, A_a (m ²)
AMX 2.0	2,01	10-VH-12S-A:7,1790-C:20,1120	1,84

Data required for CDR (EU) No 811/2013 - Reference Area A_{sol}		Data required for CDR (EU) No 812/2013 - Reference Area A_{sol}	
Collector efficiency (η_{col})	55%	Zero-loss efficiency (η_0)	0,71
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient (a_1)	3,80 W/(m ² K)
		Second-order coefficient (a_2)	0,004 W/(m ² K ²)
		Incidence angle modifier IAM (50°)	0,95
		Remark: The data given in this section are related to collector reference area (A_{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.	